

2025 Final MC Real

Consider the following incomplete method, which is intended to return the number of integers that evenly divide the integer `inputVal`. Assume that `inputVal` is greater than 0.

```
public static int numDivisors(int inputVal)
{
    int count = 0;
    for (int k = 1; k <= inputVal; k++)
    {
        if ( /* condition */ )
        {
            count++;
        }
    }
    return count;
}
```

1. Which of the following can be used to replace `/* condition */` so that `numDivisors` will work as intended?
- (A) `inputVal % k == 0`
 - (B) `k % inputVal == 0`
 - (C) `inputVal % k != 0`
 - (D) `inputVal / k == 0`
 - (E) `k / inputVal > 0`
-

Consider the following code segment.

```
for (int r = 3; r > 0; r--)
{
    int c;

    for (c = 1; c < r; c++)
    {
        System.out.print("-");
    }
    for (c = r ; c <= 3; c++)
    {
        System.out.print("*");
    }

    System.out.println();
}
```

2. What is printed as a result of executing the code segment?
-

2025 Final MC Real

- (A) --*
 -*

- (B) *-
 **

- (C) ***
 -*
 --*
- (D) ***
 **
 *-
- (E) --*

 --*
-

Assume that x and y are boolean variables and have been properly initialized.

$(x \mid \mid y) \&\& x$

3. Which of the following always evaluates to the same value as the expression?

- (A) x
(B) y
(C) $x \&\& y$
(D) $x \mid \mid y$
(E) $x != y$
-

Consider the following method, which is intended to return true if at least one of the three strings $s1$, $s2$, or $s3$ contains the substring "art". Otherwise, the method should return false.

```
public static boolean containsArt(String s1, String s2, String s3)
{
    String all = s1 + s2 + s3;
    return (all.indexOf("art") != -1);
}
```

2025 Final MC Real

4. Which of the following method calls demonstrates that the method does not work as intended?
- (A) `containsArt ("rattrap", "similar", "today")`
 - (B) `containsArt ("start", "article", "Bart")`
 - (C) `containsArt ("harm", "chortle", "crowbar")`
 - (D) `containsArt ("matriculate", "carat", "arbitrary")`
 - (E) `containsArt ("darkroom", "cartoon", "articulate")`
-

Consider the following code segment.

```
for (int outer = 1; outer <= 6; outer++)  
{  
    for (int inner = outer; inner <= 6; inner++)  
    {  
        if (inner % 2 == 0)  
        {  
            System.out.print(inner + " ");  
        }  
    }  
    System.out.println();  
}
```

5. What will be printed as a result of executing the code segment?

2025 Final MC Real

(A) $\begin{matrix} 2 & 4 & 6 \\ 4 & 6 & \\ 6 & & \end{matrix}$

(B) $\begin{matrix} 2 & 4 & 6 \\ 2 & 4 & 6 \\ 2 & 4 & 6 \end{matrix}$

(C) $\begin{matrix} 2 & 4 & 6 \\ 2 & 4 & 6 \\ 4 & 6 & \\ 4 & 6 & \\ 6 & & \\ 6 & & \end{matrix}$

(D) $\begin{matrix} 2 & 4 & 6 \\ 2 & 4 & 6 \\ 2 & 4 & 6 \\ 2 & 4 & 6 \\ 2 & 4 & 6 \\ 2 & 4 & 6 \end{matrix}$

(E) $\begin{matrix} 2 & 4 \\ 2 & 4 \\ 4 & \\ 4 & \end{matrix}$

A pair of number cubes is used in a game of chance. Each number cube has six sides, numbered from 1 to 6, inclusive, and there is an equal probability for each of the numbers to appear on the top side (indicating the cube's value) when the number cube is rolled. The following incomplete statement appears in a program that computes the sum of the values produced by rolling two number cubes.

```
int sum = / * missing code * / ;
```

6. Which of the following replacements for *missing code* would best simulate the value produced as a result of rolling two number cubes?

- (A) $2 * (\text{int}) (\text{Math.random()} * 6)$
- (B) $2 * (\text{int}) (\text{Math.random()} * 7)$
- (C) $(\text{int}) (\text{Math.random()} * 6) + (\text{int}) (\text{Math.random()} * 6)$
- (D) $(\text{int}) (\text{Math.random()} * 13)$
- (E) $2 + (\text{int}) (\text{Math.random()} * 6) + (\text{int}) (\text{Math.random()} * 6)$

2025 Final MC Real

Consider the following method.

```
public static boolean mystery(String str)
{
    String temp = "";

    for (int k = str.length(); k > 0; k--)
    {
        temp = temp + str.substring(k - 1, k);
    }

    return temp.equals(str);
}
```

7. Which of the following calls to `mystery` will return `true`?

- (A) `mystery("no")`
 - (B) `mystery("on")`
 - (C) `mystery("nnoo")`
 - (D) `mystery("nono")`
 - (E) `mystery("noon")`
-

Consider the following instance variable and method.

```
private int[] numbers;

public void mystery(int x)
{
    for (int k = 1; k < numbers.length; k = k + x)
    {
        numbers[k] = numbers[k - 1] + x;
    }
}
```

Assume that `numbers` has been initialized with the following values.

{17, 34, 21, 42, 15, 69, 48, 25, 39}

8. Which of the following represents the order of the values in `numbers` as a result of the call `mystery(3)`?

2025 Final MC Real

- (A) {17, 20, 21, 42, 45, 69, 48, 51, 39}
 - (B) {17, 20, 23, 26, 29, 32, 35, 38, 41}
 - (C) {17, 37, 21, 42, 18, 69, 48, 28, 39}
 - (D) {20, 23, 21, 42, 45, 69, 51, 54, 39}
 - (E) {20, 34, 21, 45, 15, 69, 51, 25, 39}
-

Consider the following method, `biggest`, which is intended to return the greatest of three integers. It does not always work

```
public static int biggest(int a, int b, int c)
{
    if ((a > b) && (a > c))
    {
        return a;
    }
    else if ((b > a) && (b > c))
    {
        return b;
    }
    else
    {
        return c;
    }
}
```

as intended.

9. Which of the following best describes the error in the method?
- (A) `biggest` always returns the value of `a`.
 - (B) `biggest` may not work correctly when `c` has the greatest value.
 - (C) `biggest` may not work correctly when `a` and `b` have equal values.
 - (D) `biggest` may not work correctly when `a` and `c` have equal values.
 - (E) `biggest` may not work correctly when `b` and `c` have equal values.
-

Consider the following method.

```
public static void showMe(int arg)
{
    if (arg < 10)
    {
        showMe(arg + 1);
    }
    else
    {
        System.out.print(arg + " ");
    }
}
```

2025 Final MC Real

10. What will be printed as a result of the call `showMe(0)` ?

- (A) 10
 - (B) 11
 - (C) 0 1 2 3 4 5 6 7 8 9
 - (D) 9 8 7 6 5 4 3 2 1 0
 - (E) 0 1 2 3 4 5 6 7 8 9 10
-

Consider the following method.

```
/** Precondition: values has at least one row */
public static int calculate(int[][] values)
{
    int found = values[0][0];
    int result = 0;
    for (int[] row : values)
    {
        for (int y = 0; y < row.length; y++)
        {
            if (row[y] > found)
            {
                found = row[y];
                result = y;
            }
        }
    }
    return result;
}
```

11. Which of the following best describes what is returned by the `calculate` method?

- (A) The largest value in the two-dimensional array
 - (B) The smallest value in the two-dimensional array
 - (C) The row index of an element with the largest value in the two-dimensional array
 - (D) The row index of an element with the smallest value in the two-dimensional array
 - (E) The column index of an element with the largest value in the two-dimensional array
-

2025 Final MC Real

Consider the following method.

```
/** Precondition: num > 0 */
public static int doWhat(int num)
{
    int var = 0;

    for (int loop = 1; loop <= num; loop = loop + 2)
    {
        var += loop;
    }

    return var;
}
```

12. Which of the following best describes the value returned from a call to doWhat?
- (A) num
 - (B) The sum of all integers between 1 and num, inclusive
 - (C) The sum of all even integers between 1 and num, inclusive
 - (D) The sum of all odd integers between 1 and num, inclusive
 - (E) No value is returned because of an infinite loop.
-

Consider the following code segment.

```
int x = 1;
while ( /* condition */ )
{
    if (x % 2 == 0)
    {
        System.out.print(x + " ");
    }
    x = x + 2;
}
```

The following conditions have been proposed to replace */* condition */* in the code segment.

- I. $x < 0$
 - II. $x \leq 1$
 - III. $x < 10$
-

2025 Final MC Real

13. For which of the conditions will nothing be printed?

- (A) I only
 - (B) II only
 - (C) I and II only
 - (D) I and III only
 - (E) I, II, and III
-

Consider the following method.

```
/** Precondition: arr.length > 0 */
public static int mystery(int[] arr)
{
    int index = 0;
    int count = 0;
    int m = -1;

    for (int outer = 0; outer < arr.length; outer++)
    {
        count = 0;
        for (int inner = outer + 1; inner < arr.length; inner++)
        {
            if (arr[outer] == arr[inner])
            {
                count++;
            }
        }

        if (count > m)
        {
            index = outer;
            m = count;
        }
    }

    return index;
}
```

14. Assume that `nums` has been declared and initialized as an array of integer values. Which of the following best describes the value returned by the call `mystery(nums)`?

2025 Final MC Real

- (A) The maximum value that occurs in nums
 - (B) An index of the maximum value that occurs in nums
 - (C) The number of times that the maximum value occurs in nums
 - (D) A value that occurs most often in nums
 - (E) An index of a value that occurs most often in nums
-

Consider the following definition.

```
int[][] numbers = {{1, 2, 3},  
                  {4, 5, 6}};
```

15. Which of the following code segments produces the output 123456 ?

2025 Final MC Real

- (A)

```
for (int[] row : numbers)
{
    for (int n : row)
    {
        System.out.print(n);
    }
}
```
- (B)

```
for (int[] row : numbers)
{
    for (int n : row)
    {
        System.out.print(row[n]);
    }
}
```
- (C)

```
for (int rc = 0; rc < numbers.length; rc++)
{
    System.out.print(numbers[rc]);
}
```
- (D)

```
for (int r = 0; r < numbers[0].length; r++)
{
    for (int c = 0; c < numbers.length; c++)
    {
        System.out.print(numbers[r][c]);
    }
}
```
- (E)

```
for (int c = 0; c < numbers[0].length; c++)
{
    for (int r = 0; r < numbers.length; r++)
    {
        System.out.print(numbers[r][c]);
    }
}
```
-

2025 Final MC Real

Consider the following code segment from an insertion sort program.

```
for (int j = 1; j < arr.length; j++)
{
    int insertItem = arr[j];
    int k = j - 1;

    while (k >= 0 && insertItem < arr[k])
    {
        arr[k + 1] = arr[k];
        k--;
    }

    arr[k + 1] = insertItem;

    /* end of for loop */
}
```

16. Assume that array `arr` has been defined and initialized with the values {5, 4, 3, 2, 1}. What are the values in array `arr` after two passes of the for loop (i.e., when `j = 2` at the point indicated by `/* end of for loop */`) ?
- (A) {2, 3, 4, 5, 1}
 - (B) {3, 2, 1, 4, 5}
 - (C) {3, 4, 5, 2, 1}
 - (D) {3, 5, 2, 3, 1}
 - (E) {5, 3, 4, 2, 1}
-

2025 Final MC Real

Consider the following class.

```
public class SomeMethods

{
    public void one(int first)

    { /* implementation not shown */ }

    public void one(int first, int second)

    { /* implementation not shown */ }

    public void one(int first, String second)

    { /* implementation not shown */ }

}
```

Consider the following methods.

- I. public void one(int value)
 { /* implementation not shown */ }
- II. public void one (String first, int second)
 { /* implementation not shown */ }
- III. public void one (int first, int second, int third)
 { /* implementation not shown */ }

17. Which of the following methods can be added to the SomeMethods class without causing a compile-time error?

- (A) I only
 - (B) I and II only
 - (C) I and III only
 - (D) II and III only
 - (E) I, II, and III
-

2025 Final MC Real

Consider the following two methods, which appear within a single class.

```
public static void changeIt(int[] arr, int val, String word)
{
    arr = new int[5];
    val = 0;
    word = word.substring(0, 5);

    for (int k = 0; k < arr.length; k++)
    {
        arr[k] = 0;
    }
}
```

```
public static void start()
{
    int[] nums = {1, 2, 3, 4, 5};
    int value = 6;
    String name = "blackboard";

    changeIt(nums, value, name);

    for (int k = 0; k < nums.length; k++)
    {
        System.out.print(nums[k] + " ");
    }

    System.out.print(value + " ");
    System.out.print(name);
}
```

18. What is printed as a result of the call `start()` ?

- (A) 0 0 0 0 0 0 black
 - (B) 0 0 0 0 0 6 blackboard
 - (C) 1 2 3 4 5 6 black
 - (D) 1 2 3 4 5 0 black
 - (E) 1 2 3 4 5 6 blackboard
-

2025 Final MC Real

Directions: Select the choice that best fits each statement. The following question(s) refer to the following information.

Consider the following sort method. This method correctly sorts the elements of array data into increasing order.

```
public static void sort(int[] data)
{
    for (int j = 0; j < data.length - 1; j++)
    {
        int m = j;
        for (int k = j + 1; k < data.length; k++)
        {
            if (data[k] < data[m])    /* Compare values */
            {
                m = k;
            }
        }
        int temp = data[m];          /* Assign to temp */
        data[m] = data[j];
        data[j] = temp;

        /* End of outer loop */
    }
}
```

19. Assume that sort is called with the array {6, 3, 2, 5, 4, 1}. What will the value of data be after three passes of the outer loop (i.e., when $j = 2$ at the point indicated by */* End of outer loop */*) ?
- (A) {1, 2, 3, 4, 5, 6}
 - (B) {1, 2, 3, 5, 4, 6}
 - (C) {1, 2, 3, 6, 5, 4}
 - (D) {1, 3, 2, 4, 5, 6}
 - (E) {1, 3, 2, 5, 4, 6}
-

2025 Final MC Real

The price per box of ink pens advertised in an office supply catalog is based on the number of boxes ordered. The following table shows the pricing.

Number of Boxes	Price per Box
1 up to but not including 5	\$5.00
5 up to but not including 10	\$3.00
10 or more	\$1.50

The following incomplete method is intended to return the total cost of an order based on the value of the parameter numBoxes.

```
/** Precondition: numBoxes > 0 */
public static double getCost(int numBoxes)
{
    double totalCost = 0.0;

    /* missing code */

    return totalCost;
}
```

Consider the following code segments.

```
I.  if (numBoxes >= 10)
    {
        totalCost = numBoxes * 1.50;
    }
    if (numBoxes >= 5)
    {
        totalCost = numBoxes * 3.00;
    }
    if (numBoxes > 0)
    {
        totalCost = numBoxes * 5.00;
    }
```

2025 Final MC Real

II.

```
if (numBoxes >= 10)
{
    totalCost = numBoxes * 1.50;
}
else if (numBoxes >= 5)
{
    totalCost = numBoxes * 3.00;
}
else
{
    totalCost = numBoxes * 5.00;
}
```

III.

```
if (numBoxes > 0)
{
    totalCost = numBoxes * 5.00;
}
else if (numBoxes >= 5)
{
    totalCost = numBoxes * 3.00;
}
else if (numBoxes >= 10)
{
    totalCost = numBoxes * 1.50;
}
```

20. Which of the following code segments can be used to replace */* missing code */* so that method `getCost` will work as intended?
- (A) I only
 - (B) II only
 - (C) III only
 - (D) I and II
 - (E) II and III
-

2025 Final MC Real

Consider the following code segment.

```
String[][] board = new String[5][5];

for (int row = 0; row < 5; row++)
{
    for (int col = 0; col < 5; col++)
    {
        board[row][col] = "O";
    }
}

for (int val = 0; val < 5; val++)
{
    if (val % 2 == 1)
    {
        int row = val;
        int col = 0;
        while (col < 5 && row >= 0)
        {
            board[row][col] = "X";
            col++;
            row--;
        }
    }
}
```

21. Which of the following represents board after this code segment is executed?

2025 Final MC Real

(A)

	0	1	2	3	4
0	X	○	X	○	X
1	○	X	○	X	○
2	X	○	X	○	X
3	○	X	○	X	○
4	X	○	X	○	X

(B)

	0	1	2	3	4
0	○	X	○	X	○
1	X	○	X	○	X
2	○	X	○	X	○
3	X	○	X	○	X
4	○	X	○	X	○

(C)

	0	1	2	3	4
0	X	○	○	○	X
1	○	X	○	X	○
2	○	○	X	○	○
3	○	X	○	X	○
4	X	○	○	○	X

(D)

	0	1	2	3	4
0	○	X	○	○	○
1	○	○	X	○	○
2	X	○	○	X	○
3	○	X	○	○	X
4	○	○	X	○	○

(E)

	0	1	2	3	4
0	○	X	○	X	○
1	X	○	X	○	○
2	○	X	○	○	○
3	X	○	○	○	○
4	○	○	○	○	○

2025 Final MC Real

Consider the following class declaration.

```
public class StudentInfo
{
    private String major;
    private int age;

    public String getMajor()
    { return major; }

    public int getAge()
    { return age; }

    // There may be instance variables, constructors, and methods that are not shown.
}
```

The following instance variable and method appear in another class.

```
private List<StudentInfo> students;

/** @return the average age of students with the given major;
 *      -1.0 if no such students exist
 */
public double averageAgeInMajor(String theMajor)
{
    double sum = 0.0;
    int count = 0;
    for (StudentInfo k : students)
    {
        /* missing code */
    }

    if (count > 0)
    {
        return sum / count;
    }
    else
    {
        return -1.0;
    }
}
```

22. Which of the following could be used to replace */* missing code */* so that `averageAgeInMajor` will compile without error?

2025 Final MC Real

- (A)

```
if (theMajor.equals(k.major))
{
    sum += k.age;
    count++;
}
```
- (B)

```
if (theMajor.equals(k.getMajor()))
{
    sum += k.getAge();
    count++;
}
```
- (C)

```
if (theMajor.equals(k.major))
{
    sum += k.getAge();
    count++;
}
```
- (D)

```
if (theMajor.equals(students[k].getMajor()))
{
    sum += students[k].getAge();
    count++;
}
```
- (E)

```
if (theMajor.equals(getMajor(k)))
{
    sum += getAge(k);
    count++;
}
```
-

2025 Final MC Real

Consider the problem of finding the maximum value in an array of integers. The following code segments are proposed solutions to the problem. Assume that the variable `arr` has been defined as an array of `int` values and has been initialized with one or more values.

```
I.  int max = Integer.MIN_VALUE;
    for (int value : arr)
    {
        if (max < value)
        {
            max = value;
        }
    }
```

```
II.  int max = 0;
    boolean first = true;
    for (int value : arr)
    {
        if (first)
        {
            max = value;
            first = false;
        }
        else if (max < value)
        {
            max = value;
        }
    }
```

```
III. int max = arr[0];
    for (int k = 1; k < arr.length; k++)
    {
        if (max < arr[k])
        {
            max = arr[k];
        }
    }
```

23. Which of the code segments will always correctly assign the maximum element of the array to the variable `max`?
- (A) I only
 - (B) II only
 - (C) III only
 - (D) II and III only
 - (E) I, II, and III
-
-

2025 Final MC Real

Consider the following instance variable and method. Method `wordsWithCommas` is intended to return a string containing all the words in `listOfWords` separated by commas and enclosed in braces. For example, if `listOfWords` contains ["one", "two", "three"], the string returned by the call `wordsWithCommas ()` should be "{one, two, three}".

```
private List<String> listOfWords;

public String wordsWithCommas()
{
    String result = "{";

    int sizeOfList = /* expression */ ;

    for (int k = 0; k < sizeOfList; k++)
    {
        result = result + listOfWords.get(k);

        if ( /* condition */ )
        {
            result = result + ", ";
        }
    }

    result = result + "}";
    return result;
}
```

24. Which of the following can be used to replace `/* expression */` and `/* condition */` so that `wordsWithCommas` will work as intended?
- (A) `/* expression */` `listOfWords.size() - 1 / k != 0`
`/* condition */`
 - (B) `/* expression */` `listOfWords.size() / k != 0`
`/* condition */`
 - (C) `/* expression */` `listOfWords.size() - 1 / k != sizeOfList - 1`
`/* condition */`
 - (D) `/* expression */` `listOfWords.size() / k != sizeOfList - 1`
`/* condition */`
 - (E) `/* expression */` `result.length() / k != 0`
`/* condition */`

2025 Final MC Real

Directions: Select the choice that best fits each statement. The following question(s) refer to the following information

Consider the following `binarySearch` method. The method correctly performs a binary search.

```
/** Precondition: data is sorted in increasing order. */
public static int binarySearch(int[] data, int target)
{
    int start = 0;
    int end = data.length - 1;
    while (start <= end)
    {
        int mid = (start + end) / 2;      /* Calculate midpoint */
        if (target < data[mid])
        {
            end = mid - 1;
        }
        else if (target > data[mid])
        {
            start = mid + 1;
        }
        else
        {
            return mid;
        }
    }
    return -1;
}
```

25. Consider the following code segment.

```
int [ ] values = {1, 2, 3, 4, 5, 8, 8, 8}; int target = 8;
```

What value is returned by the call `binarySearch (values, target)` ?

- (A) -1
- (B) 3
- (C) 5
- (D) 6
- (E) 8

2025 Final MC Real

Consider the following incomplete method that is intended to return a string formed by concatenating elements from the parameter words. The elements to be concatenated start with startIndex and continue through the last element of words and should appear in reverse order in the resulting string.

```
/** Precondition: words.length > 0;  
 *           startIndex >= 0  
 */  
public static String concatWords(String[] words, int startIndex)  
{  
    String result = "";  
  
    /* missing code */  
  
    return result;  
}
```

For example, the following code segment uses a call to the concatWords method.

```
String[] things = {"Bear", "Apple", "Gorilla", "House", "Car"};  
System.out.println(concatWords(things, 2));
```

When the code segment is executed, the string "CarHouseGorilla" is printed.

The following three code segments have been proposed as replacements for */* missing code */*.

2025 Final MC Real

- I.

```
for (int k = startIndex; k < words.length; k++)  
{  
    result += words[k] + words[words.length - k - 1];  
}
```
- II.

```
int k = words.length - 1;  
while (k >= startIndex)  
{  
    result += words[k];  
    k--;  
}
```
- III.

```
String[] temp = new String[words.length];  
for (int k = 0; k <= words.length / 2; k++)  
{  
    temp[k] = words[words.length - k - 1];  
    temp[words.length - k - 1] = words[k];  
}  
  
for (int k = 0; k < temp.length - startIndex; k++)  
{  
    result += temp[k];  
}
```

26. Which of these code segments can be used to replace */* missing code */* so that `concatWords` will work as intended?
- (A) I only
(B) II only
(C) III only
(D) I and II
(E) II and III
-

2025 Final MC Real

Consider the following code segment.

```
List<String> students = new ArrayList<String>();

students.add("Alex");
students.add("Bob");
students.add("Carl");

for (int k = 0; k < students.size(); k++)
{
    System.out.print(students.set(k, "Alex") + "  ");
}

System.out.println();

for (String str : students)
{
    System.out.print(str + "  ");
}
```

27. What is printed as a result of executing the code segment?
- (A) Alex Alex Alex
Alex Alex Alex
 - (B) Alex Alex Alex
Alex Bob Carl
 - (C) Alex Bob Carl
Alex Alex Alex
 - (D) Alex Bob Carl
Alex Bob Carl
 - (E) Nothing is printed because the first print statement will cause a runtime exception to be thrown.
-

2025 Final MC Real

Consider the following two classes.

```
public class A
{
    public void show()
    {
        System.out.print("A");
    }
}
```

```
public class B extends A
{
    public void show()
    {
        System.out.print("B");
    }
}
```

Consider the following code segment.

```
A obj = new B();
obj.show();
```

- 28.** What is printed as a result of executing the following code segment?
- (A) A
 - (B) B
 - (C) AB
 - (D) BA
 - (E) The code results in a runtime error.
-